## SEBASTIAN SLOT-VENT SINKS SEBASTIAN PVC ADA SLOT-VENT WALK-AROUND PRINT PROCESSING SINKS

THESE SEBASTIAN WALK-AROUND DARKROOM SINKS ARE EQUIPPED WITH THE ULTIMATE CHEMICAL FUME EXHAUST SYSTEM. AT TRAY-LEVEL, CHEMICAL FUMES ARE REMOVED THROUGH CONTINUOUS SLOTS IN THE SINK RAILS AND EVACUATED THROUGH A DUCT SYSTEM UNDER THE SINK. CONSTRUCTED ENTIRELY OF PVC PLASTIC, INERT TO ALL DARKROOM CHEMICALS, THESE SINKS ARE IN COMPLIANCE WITH ALL ADA GUIDELINES USING THE SIDE-APPROACH. THESE VENTED WALK-AROUND SINKS ARE ENGINEERED AND FABRICATED TO BE "STATE-OF-THE-ART" FOR TEACHING AND LEARNING DARKROOM PHOTOGRAPHY.

- DESIGN FEATURES A HIGHLY EFFICIENT FUME EXHAUST PATH YIELDING LOWEST POSSIBLE PRESSURE LOSS AND LOWEST OPERATIONAL COST.
- THESE SINKS CAN BE FITTED WITH MANY OPTIONAL FAUCETS, WATER REGULATORS.
   EYE-WASH UNITS, CHILLERS, DILUTION-NEUTRALIZATION TANKS, SILVER RECOVERY SYSTEMS - SEE CAT. PGS 2-20 \$ 2-21.
- THERE ARE PRINT WASHERS THAT ATTACH TO THESE SINKS, (SEE CAT. PG. 3-4 TO 3-10), PRINT WASHER WITH A SHELF TO HOLD "RC" PRINT DRYERS (SEE CAT. PG. 3-9) AND A PRINT WASHER WITH A SQUEEGEE BOARD (SEE CAT. PG. 3-10)
- THIS DESIGN IS SO UNIQUELY SIMPLE THAT ON SITE INSTALLATION CAN BE DONE BY A LOCAL HVAC TECHNICAN
- HEAVY-DUTY PVC LEGS SUPPORT THE WALK-AROUND SINK (AND WASHER) AND CAN BE FASTENED TO THE FLOOR WITH #LDTS-383 TAPCON SS FASTENERS

## SLOT-VENTED WALK-AROUND SINK DATA

FEATURES OF THREE "SWASSY" SINKS	SINK MODEL SWASSV- 6756	SINK MODEL SWASSV- 9156	SINK MODEL SWASSV- 12756	SINK MODEL SWASSV- 15756
OA SINK SIZE:	67x55.5"	97x55.5"	127x55.5"	157x55.5"
SINK + MAIN DUCTS:	84x55.5"	112x55.5"	150"x55.5"	194"x55.5"
USEABLE AREA:	60"x47"	90"x47"	120"x47"	150"x47"
PLENUMS per SIDE:	TWO	THREE	FOUR	FIVE
MAIN DUCTS (2):	8"4	10"4	12"Ф	Ι4"Φ
cfm per PLENUM:	245cfm	245cfm	245cfm	245cfm
cfm per SINK SIDE:	490cfm	735cPm	980cfm	1,225cfm
cfm TOTAL SINK:	980cfm	1,479cfm	1,960cfm	2,450cfm

 PLUMBING FIXTURES ARE OPTIONAL: ILLUSTRATED HERE ARE TWO L-22IIVB-BH MIXING FAUCETS AND AN AUTO-FLOW EYE AND FACE WASH UNIT, ALL DECK MOUNTED (SEE CAT. PAGE 2-20 FOR OPTIONS)

> THIS SINK IS DESIGNED SO THAT PLENUMS ARE EASILY DRAINED AND DUCTS EASILY CLEANED.
>  POST INSTALLATION AIR BALANCING IS EASILY ACCOMPLISHED WITH INSTALLED SLIDE DAMPERS.

 STANDARD DRAINS ILLUSTRATED: 1-1/2" PVC SINK DRAIN WITH STRAINER (NO STANDPIPE PROVIDED) AND "SPENT-FIX" DUMP TROUGH WITH 1-1/2" to 1" MALE HOSE ADAPTER WITH STRAINER AND CAP

DO NOT USE SOLVENTS IN PVC SINKS

CALIFORNIA STAINLESS MFG. 888-712-7035

PRODUCTS'

SEBASTIAN DARKROOM PRODUCTST

DIVISION OF CALIFORNIA STAINLESS MFG., INC.
UNIQUE, INNOVATIVE & ENGINEERED TO WORK
TOLL FREE (888) 712-7035 FAX (805) 484-1030

calstanless@aol.com www.sebastlandarkroomprod.com